

Skirt With Decorative Yoke - Sewing Pattern #2370

Recommendations on fabric: thin natural/mixed suiting fabrics.

You will also need: fusible interfacing, dress zipper, 2 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem - 1.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front skirt - cut 2
3. Front yoke - cut 2
4. Back yoke - cut 4
5. Side - cut 2
6. Pocket bag - cut 2
7. Trimming - cut 2

Fusible interfacing:

1. Back yoke - cut 2
2. Front yoke - cut 1

3. Trimming – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing. Apply fusible interfacing to pocket opening on front skirt.
2. Sew back yoke to back skirt, press towards top. Serge center back edges separately. Sew center seam from notch for zipper to hem. Press seam apart. Sew in zipper.
3. Fold trimming in half lengthwise right sides together and sew the shorter edge. Turn the piece right side out, straighten, press.
4. Pin pocket bag to front skirt right sides together and sew pocket opening, inserting trimming. Clip seam allowances, fold pocket bag onto wrong side, press. Pin front skirt at side and sew edges of pocket bags, serge. Baste pieces together along the side edge and upper edge.
5. Sew center seam on front skirt, press towards left and serge. Sew front yoke to front skirt, press towards top.
6. Sew side seams, press seams towards back and serge.
7. Sew side seams of inside yokes, press seam apart. Serge lower edge. Pin yoke onto skirt right sides together and sew upper edge. Seam Allowances topstitch at yoke at 0.2 cm from the seam. Fold yoke onto the wrong side, press. Fold inside center edges and sew to zipper tape. Topstitch yoke into the seam of outer yoke (stitch-in-the-ditch).
8. Serge lower edge of garment, press onto wrong side and topstitch.
9. Sew on buttons, fixing trimming on front skirt.

TECHNICAL DRAWING:

