

Blouse With Yoke And One-Piece Sleeve - Sewing Pattern #2392

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing; 6 buttons; elastic tape, its width should equal 1 cm.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment - 2 cm. Seam allowance on lower edge of sleeve - 2.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Back yoke - cut 1 on fold
3. Front - cut 2
4. Front yoke - cut 2
5. Back sleeve - cut 2
6. Front sleeve - cut 2

7. Stand collar — cut 2
8. Center front facing – cut 2
9. Casing for drawstring – cut 1 on fold
10. Belt – cut 1 on fold

Fusible interfacing:

1. Stand collar – cut 1
2. Center front facing – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Pin stand collars together right sides together sew outer edges. Start and stop sewing exactly at the marked line of seam. Clip into curves. Turn the finished stand collar right side out and press.
3. Sew a gathering stitch along the upper edge of the back and gather fullness. Sew Back Sleeve to Back, serge and press. Sew back yoke to yoke, press towards top and serge.
4. Sew a gathering stitch along upper edge of front and gather fullness. Sew Front Sleeve to Front, serge and press. Sew front yoke to front, press towards top and serge.
5. Sew upper sleeve seam, press seams towards back and serge. Sew the lower sleeve seam and continue sewing the side seam, press seams towards back and serge.
6. Serge the shorter edges of casing, turn inside and topstitch. Fold the longer edges of casing onto wrong side and press. Pin casing, wrong side down, onto front and back according to the markings and topstitch.
7. Serge the shoulder edge and the inner edge of center front facing. Pin button stand (center front facing) to front right sides together and sew center front edge and upper corner. Clip into seam allowance near the notch, turn center front facing onto wrong side, straighten, press. Baste center front facing to front along the neckline edge.
8. Sew outer stand collar into neckline, press seam allowances at stand collar. Turn under the raw edge of inner stand collar and stitch in the ditch.
9. Serge lower edge of garment, press onto wrong side and topstitch.
10. Make buttonholes on right front. Sew on buttons on the left one.
11. Fold under the lower edge of sleeve by 1 cm, then again at 1.5 cm and topstitch, leaving an opening for elastic tape. Thread elastic tape into the resulting casing, slipstitch.

12. Fold belt in half lengthwise right sides together and sew, and leave an opening unsewn along the lower edge, so that you can turn out the piece later. Turn belt right side out, straighten and press. Topstitch belt around all edges at 0.1 cm from the edge. Thread it into casing.

TECHNICAL DRAWING:

