

Sewing Pattern — Skirt 5996

Recommendations on fabric: natural/mixed thin woolen fabric.

You will also need: fusing; blind zipper, 1 button.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment - 2 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central front part – 1 detail
2. Side front part – 2 details
3. Back part – 2 details
4. Belt – 1 detail

Fusing:

1. Belt – 1 detail

INSTRUCTIONS:

1. Apply fusing to belt.
2. Stitch loosely along side and center edges of side front part from the top up to lower notch and gather ruffles. Stitch side part of the front to central part, press seam onto central part, serge.
3. Sew darts on back part. Press depths towards center. Serge seam allowances of center edge. Sew center edge of back part from zipper marker up to hem. Press apart the seam. Sew in zipper.
4. Sew side seams. Serge and press seam allowances towards back part.
5. Stitch belt to top edge of the skirt. Overstitch ends of the belt, slash seam allowances in corners and turn out. Turn inside inner edge of the belt and topstitch into connecting seam. Press ready belt.

6. Serge lower edge of the skirt, press onto wrong side and topstitch.
7. Mark and make a buttonhole (on the belt). Sew a button.

TECHNICAL DRAWING:

