

## Sewing Pattern — Sheepskin coat 5994

Recommendations on fabric: faux sheepskin.

You will also need: 9 buttons, 8 under buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along all open edges (edge of buttonstand, hem of the garment, edge of cuff, upper edge of off-set welt, ends and outer edge of collar, upper edge of stand-up part of collar) - 0 cm; other seam allowances - 1.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



ATTENTION: Princess seams of back part and of front part, center seam of back part, off-set welt connecting seam, sleeve connecting seam, collar and stand-up part of collar connecting seam, neckline and stand-up part of collar connecting seam are worked with lap seam. Seam allowance on one of the details is cut off by that (see instructions).

### **CUTTING:**

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central front part – 2 details
5. Stand-up part of collar – 1 detail
6. Collar – 1 detail
7. Sleeve – 2 details
8. Cuff – 2 details
9. Pocket – 2 details
10. Off-set welt – 2 details

## **INSTRUCTIONS:**

1. Stitch off-set welt to the pocket with lap seam. Put fixing stitch along top edge of off-set welt. Put the pocket onto side front part according to markers and topstitch.
2. Sew princess edges on front part with lap seam.
3. Sew princess seams on back part with lap seam.
4. Sew center edge of back part with lap seam.
5. Sew shoulder seams of the coat.
6. Sew sleeve into open armhole with lap seam.
7. Sew side seams of the coat together with the edge of sleeve.
8. Sew cuff into ring. Put fixing stitch along top edge of cuff. Fold sleeve and cuff with fur inside and stitch cuff to the sleeve with closed seam (cut cuff seam allowance and sleeve topstitch seam allowance). Fold cuff onto right side.
9. Stitch collar to stand-up part of collar with lap seam. Sew stand-up part of collar into the neckline with lap seam (finish the stitch on right front part, near the notch)
10. Put fixing stitch along edge of buttonstand, edge of collar, and along hem line.
11. Serge buttonholes on right front part and on stand-up part of collar, sew buttons. Sew on buttons symmetrical to buttonholes on right front part. Please note that buttons on front part are sewn on with under buttons.

## **TECHNICAL DRAWING:**

