

Skirt With High Waist - Sewing Pattern #2452

Recommendations on fabric: natural/mixed fabrics suitable for skirts.

You will also need: lining, fusible interfacing, 3 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem - 3 cm, seam allowance along lower edge of lining - 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front left skirt - cut 1
3. Front right skirt - cut 1
4. Front facing - cut 1
5. Back facing - cut 2
6. Flap - cut 1

Lining:

1. Front lining - cut 1 on fold
2. Back lining - cut 2

Fusible interfacing:

1. Back facing - cut 2
2. Front facing - cut 1
3. Flap - cut 1

Attention! Pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric-some of the pattern blocks need to be laid onto fabric with their wrong side on top.

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew darts on back skirts. Press bulk towards center. Serge center back edges separately, serging the vent at the same time. Sew center edge from zipper marking up to the vent corner. Press seam apart, press seam allowances of the vent towards left side seam. Press right side of vent at 1 cm and topstitch. Sew together vent seam allowances by machine stitch. Sew in zipper.
3. Pin together flap in half lengthwise right sides together and sew lower edge. Flap turn right side out, straighten, press. Pin flap onto the right side of left skirt, match the princess seam edges and baste together along the seam.
4. Sew dart on right front skirt. Press bulk towards center. Sew side front to front. Serge seam and press towards center.
5. Sew side seams, press seams towards back and serge.
6. Sew darts on lining. Press bulk towards center. Sew side seams of lining. Serge seams and press towards back. Serge separately center edges of lining. Sew center back edges from notch for zipper to bottom, press seam apart. Fold seam allowance for hem under two times by 1 cm and topstitch.
7. Sew side edges of facings. Press seam apart. Sew lining to facings. Press seam allowance towards bottom. Pin facing to skirt right sides together and sew upper edge. Fold facing and lining onto wrong side, straighten, press.
8. Sew lining to side edge by hand. Slipstitch lining to zipper tape.
9. Serge lower edge of garment, press onto wrong side and finish with hidden stitches.

10. Sew on buttons, fixing the flap.

TECHNICAL DRAWING:

