

## Sewing Pattern — Skirt 5987

Recommendations on fabric: denim

You will also need: zipper of 8 cm long, 4 buttons.

Seam allowances: all seams - 1 cm, hem— 2.5 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



### **CUTTING:**

#### Main fabric:

1. Center upper back - cut 2
2. Center lower back — cut 2
3. Side upper back – cut 2
4. Side lower back – cut 2
5. Center upper right front – cut 1
6. Center upper left front — cut 1
7. Center lower right front – cut 1
8. Center lower left front – cut 1
9. Side upper front – cut 2
10. Side lower front – cut 2
11. Back facing – cut 1
12. Front left facing – cut 1
13. Front right facing – cut 1
14. Belt loop – cut 1
15. Button fly – cut 1

---

## **INSTRUCTIONS:**

1. Sew center upper and side backs to corresponding lower parts, press seams upwards and serge. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam. Sew center and side backs, press seams toward center and serge. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam.
2. Serge center back edges. Sew back center seam from top down to slit mark. Trim seam near the mark. Press upper part to left side, press the slit. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam, from top down to slit, stop stitch and go to left side of the slit. Stitch right side of the slit at 0.1 cm from the edge.
3. Serge center edges of center lower fronts together with one-piece facings. Sew front center seam from hem up to the fly-piece mark. Press seam toward right side seam. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam.
4. Press fly-piece on right center lower front to wrong side. On left side press seam at 1 cm, leaving a ledge. Sew zipper from left side into the edge, placing blades edge-to-edge with the fold. Serge longitudinal and lower edges of the button fly. Lay unfolded button fly under closure seam edge from the left side and topstitch facing onto button fly close to the zipper connecting seam. Unfold front panel, straighten closure edge. Match front center lines and tack. Sew free tape of zipper to one-piece facing of the right half without catching the front panel.
5. Serge center edges of upper center fronts. Sew center and side upper parts to corresponding lower parts, press seams upwards and serge. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam. Sew center and side fronts, press seams toward center and serge. Make double decorative stitch at 0.1 cm and 0.7 cm from the seam.
6. Sew side edges of the skirt. Press seams onto back panel, serge.
7. Sew side edges of facings. Press apart seams. Serge outer edge of the facing. Sew facing to one-piece front facings. Place facing on skirt right sides together and stitch upper edge. Trim seams in corners, turn facing wrong side out.
8. Stitch front right panel along zipper closure as marked, leaving 3 cm to lower edge of closure. Zip up and continue decorative stitch curving at the end, catching the button fly. Make double decorative stitch at 0.1 cm and 0.7 cm from upper edge of the skirt.
9. Serge hem of the skirt, press to wrong side and topstitch.
10. Serge long side of belt loop. Turn unserged edge inside and close with the serged edge. Make two parallel stitches at 0.1 cm from the edge. Cut several belt loops. Sew belt loops to seams as marked.
11. Serge button holes on fly piece, sew on buttons on button fly.

**TECHNICAL DRAWING:**

