

Sewing Pattern — Skirt 5984

Recommendations on fabric: natural or mixed woolen fabric

You will also need: interfacing, blind zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: all seams - 1 cm, hem of the garment - 1.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central front part – 1 detail
2. Side front part – 2 details
3. Central back part – 1 detail
4. Side back part – 2 details
5. Front facing – 1 detail
6. Back facing – 1 detail

Interfacing:

1. Front facing – 1 detail
2. Back facing – 1 detail

INSTRUCTIONS:

1. Apply interfacing to facings.
2. Sew cord edges on front part from the top up to slit marker. Slash seam allowance near slit marker on details of side front part. Finish section from marker downwards. Finish seam allowance of cord seam and press onto central part. Put decorative stitch on central part up to hem at 0.1 cm off the seam. On side part, put the stitch along slit t 0.1 off the edge.
3. Sew cord edges on back part. Finish and press the seam towards center.

4. Finish separately left side edges of back and front part. Sew left side edge from zipper marker downwards. Press seam allowances apart and press slits for zipper. Sew zipper into left side seam of the skirt. Sew, press towards back part and finish right side seam .
5. Sew right side seam on details of the facings, press seam allowances apart. Finish lower edge of the facings. Stitch the facing to skirt. Slash seam allowances. Direct seam allowance onto the facing and put the stitch at 0.3 off the seam. Fasten the facing by hand at side and cord seams' level.
6. Finish lower edge of the skirt, press onto wrong side and topstitch.

TECHNICAL DRAWING:

