

## Denim Jacket With Trimming - Sewing Pattern #2506

Recommendations on fabric: natural/mixed jeans fabrics;  
contrasting fabric for decoration.

You will also need: fusible interfacing; 4 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of  
garment - 2.5 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Upper front - cut 2
5. Center front - cut 2
6. Upper sleeve - cut 2
7. Lower sleeve - cut 2

8. Cuff - cut 2
9. Center front facing - cut 2
10. Lapel - cut 4
11. Stand collar - cut 2
12. Back neck facing - cut 1

Decorative fabric:

1. Front inset - cut 2

Fusible interfacing:

1. Center front facing - cut 2
2. Lapel - cut 2
3. Back neck facing - cut 1

## **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew side backs to center back, press towards center, serge and topstitch at 0.5 cm from seam. Sew center back seam, press towards left, serge and topstitch at 0.5 cm from seam.
3. Sew upper front to side front, press towards top, serge and topstitch at 0.5 cm from seam. Sew side fronts to front, press towards center, serge and topstitch at 0.5 cm from seam.
4. Sew front inset to garment to front, clipping into seam allowance near corner. Press seam allowances towards inset, serge.
5. Sew shoulder and side seams, press seam allowances towards back and serge.
6. Pin lapels together, right sides together and sew outer edge. Clip seam allowances, turn the lapels right side out, straighten and press. Pin stand collars together right sides together and sew outer edge. Clip seam allowances, turn stand collar right side out, straighten and press.
7. Pin lapels onto center front and topstitch at neckline edge. Sew the stand collar into neckline.
8. Sew shoulder edges of center front facings and back neckline facing, press seam apart. Serge outer edge. Pin center front facing onto main piece, right sides together, pin together and sew buttonstand, front neckline, back neckline and lower edge. When stitching make sure to place the front piece on top. Topstitch seam allowance on buttonstand onto buttonstand. Place stitch line at 0,2 cm from seam. Turn center front facing onto wrong side, straighten, press. Baste to the main piece along the shoulder edges.
9. Sew the elbow edges of the sleeve separately. Sew the elbow seam of sleeve from the cap to the mark, clip

into seam allowance near the notch. Press the seam allowance on the area from sleeve cap to mark and sew a decorative stitch along the seam at 0.5 cm. Press apart the seam allowances on the area from the mark down to hem and sew decorative stitch along the edges at 0.1 cm. Sew front seam on sleeve, press seam allowances towards lower part and serge. Sew sleeves into armholes matching notches, serge and press.

10. Fold cuffs in half lengthwise right sides together and sew short sides. Start and stop stitching exactly at the marked line of the cuff seam. Turn cuff right side out, straighten and press. Sew outer side of cuff to lower edge of sleeve, press towards cuff. Fold the seam allowance of the inner side onto the wrong side and press and stitch in the ditch.

11. Make buttonholes on right front, sew on buttons on left front. Make buttonholes and sew on buttons onto cuffs.

## **TECHNICAL DRAWING:**

