

Sweatshirt With Princess Seams - Sewing Pattern #2520

Recommendations on fabric: fleece, flannel or thick natural/mixed knit fabric of small stretchiness. For decoration – knit fabric of high stretchiness in a matching color.

You will also need: closure-zipper.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Center front - cut 1 on fold
3. Side front - cut 2
4. Front yoke - cut 2
5. Sleeve - cut 2
6. Stand collar - cut 2
7. Off-set welt - cut 2

8. Large pocket bag - cut 1
9. Small pocket bag - cut 1

Main fabric 1:

1. Hem facing - cut 1 on fold
2. Cuff - cut 2

INSTRUCTIONS:

1. Sew front yoke to front along the vertical edges up to the horizontal line. Clip into the corner of seam allowance on front and serge.
2. Press welt in half lengthwise wrong sides together. Pin off-set welt onto the right side of center front and sew. Start and stop stitching exactly at the horizontal lines of the off-set welt. Trim away corners, fold the off-set welt onto the right side, straighten, press. Sew the shorter ends of the off-set welt to the horizontal seam allowances of the front.
3. Serge the side edges of the smaller pocket bag. Sew the smaller pocket bag into the seam of the off-set welts, press seam. Pin the bigger pocket bag onto the smaller pocket bag and sew upper edge. Press seam, serge. Slipstitch the bigger pocket bag to center front along the princess seam edge and the lower edge.
4. Sew side fronts to front, press towards side seam and serge.
5. Sew shoulder seams, press seams towards back and serge.
6. Sew outer stand collar into neckline, slightly stretching it stand collar, press seam allowances at stand collar. Sew in zipper. Serge lower edge of inner stand collar. Pin the inner stand collar, right side down, onto the outer stand collar and sew upper edge. Fold away stand collar onto wrong side and press. Stitch in the ditch the lower edge of the inner collar into the seam. Slipstitch the center edge of inner stand collar to the zipper tape. Sew a decorative stitch along the zipper teeth at 0.5 cm.
7. Close the zipper. Sew the lower edge of the front yoke to front, serge and press towards bottom.
8. Sew sleeves to garment, matching notches, serge and press. Sew sleeve seams and continue sewing side seams, serge and press.
9. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to sleeve, slightly stretching the cuff, serge.
10. Sew lower facing into a ring, press seam apart. Fold facing in half lengthwise wrong sides together and press. Sew the facing to the hem, slightly stretching the facing, serge.

TECHNICAL DRAWING:

