

## Blouse With One-Piece Cuff - Sewing Pattern #2547

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment - 1.5 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Back - cut 1 on fold
2. Front - cut 1 on fold
3. Front neck facing - cut 1
4. Back neck facing - cut 1

Fusible interfacing:

1. Front neck facing - cut 1
2. Back neck facing - cut 1

### **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew shoulder and side seams, press seams towards back and serge.
3. Sew the shoulder seams of the neckline facings. Press seam apart. Serge outer edge. Pin facing onto garment right side down and sew neckline, clipping into corner. Clip seam allowances, fold facing onto wrong side and press.
4. Serge lower edge of sleeve. Fold the cuff onto wrong side and press and press the fold. Sew cuff to sleeve. Fold cuff to right side and press. Sew the cuff to the side seam and to the shoulder seam by hand.
5. Serge lower edge of garment, press onto wrong side and topstitch.

### **TECHNICAL DRAWING:**

