

## Asymmetrical Jacket - Sewing Pattern #2586

Recommendations on fabric: natural/mixed knit fabric of small stretchiness in contrasting colors.

You will also need: fusible interfacing; shoulder pads; 1 button.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve - 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric-some of the pattern blocks need to be laid onto fabric with their wrong side on top!

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Center front right - cut 1

5. Center front left – cut 1
6. Sleeve – cut 2
7. Center front facing left – cut 1
8. Back neck facing – cut 1

Main fabric 1:

1. Front decoration – cut 2

Fusible interfacing:

1. Center front facing left – cut 1
2. Back neck facing – cut 1
3. Front decoration – cut 1

## **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew side backs to center back, press towards center, serge. Sew the center back seam, press towards left, serge.
3. Sew front darts, press bulk towards top. Sew side fronts to front, press towards center, serge.
4. Pin decorative pieces together, right sides together and sew center front edge and lower edge. Trim away corners, turn the piece right side out, press. Sew the decorative piece to the right front, press the seam allowances towards the main piece and serge.
5. Serge outer edge of center front facing. Pin the center front facing to the left front and sew center front edge and lower edge. Trim away corners, turn the piece right side out, press.
6. Serge outer edge of back neckline facing. Pin neckline facing onto Back and sew neckline exactly up to the marked line of shoulder seam. Clip seam allowances, fold facing onto wrong side and press.
7. Sew shoulder seams, inserting the Front between the Back and the Facing, press towards the back and serge. Sew side seams, press seam allowances towards back, serge.
8. Sew sleeve seam, press seam allowances towards back, serge.
9. Sew sleeves into armholes matching notches, adjusting ease along upper side of sleeve cap. Serge and press. Sew shoulder pads.
10. Serge lower edge of garment and lower edge of sleeve, press onto wrong side and finish with hidden stitches.

11. Make buttonhole on right front, on left front sew on button.

**TECHNICAL DRAWING:**

