

Velvet Jacket - Sewing Pattern #2616

Recommendations on fabric: natural/mixed velvet fabrics.

You will also need: fusible interfacing; lining; 9 buttons.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Back yoke - cut 1
3. Front yoke - cut 2
4. Front - cut 2
5. Stand collar - cut 2
6. Placket - cut 1
7. Center front facing - cut 2

8. Upper sleeve – cut 2
9. Lower sleeve – cut 2
10. Cuff – cut 2
11. Pocket welt – cut 2
12. Large pocket bag – cut 2

Lining:

1. Small pocket bag – cut 2

Fusible interfacing:

1. Stand collar – cut 1
2. Placket – cut 1
3. Center front facing – cut 2
4. Cuff – cut 2
5. Pocket welt – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Mark the pocket and apply fusible interfacing to this area. Press welt in half lengthwise wrong sides together. Topstitch small pocket bag onto inner side of welt. Sew welt to front along lower marked line of pocket. Sew large pocket bag to front along upper marked line of pocket. Stop stitching near short marking lines of the pocket. Slash through pocket opening. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening. Turn welt and large pocket bag onto wrong side through the resulting opening. Sew a double back stitch lines near corners to fix ends of pockets. Sew together edges of pocket bags, serge.
3. Sew a gathering stitch along the upper edge of back and gather fullness. Sew back to back yoke, press seam allowances towards top and serge. Sew a decorative stitch along the seam at 0.5 cm. Sew a gathering stitch along the upper edge of front and gather fullness. Sew fronts to front yokes, press seam allowances towards top and serge. Sew a decorative stitch along the seam at 0.5 cm.
4. Serge outer edge of center front facing. Pin the center front facing to the front right sides together and sew center front edge. Press seam, fold center front facing onto wrong side and baste to the main piece along the neckline edge and the lower edge.
5. Sew shoulder and side seams, press towards the back and serge.
6. Pin together parts of stand collar, right sides together and sew the outer side. Start and stop sewing exactly at the marked line of seam between stand collar and garment. Clip seam allowances. Stand collar turn right side out, straighten and press. Sew outer stand collar into neckline, press seam allowances towards stand collar. Fold the seam allowance of the inner side onto the wrong side and press and stitch in the ditch.

7. Fold placket in half lengthwise right sides together and sew short sides. Start and stop stitching exactly at the marked line of the placket seam. Turn right side out placket onto right side, straighten, press. Sew a gathering stitch along the lower edge of garment and gather fullness. Sew the outer side of placket to the garment, press seam allowances onto placket. Fold the seam allowance of the inner side onto the wrong side and press and topstitch into seam of.
8. Serge the elbow edges of the sleeve separately. Sew the elbow seam of sleeve from the cap to the mark, clip into seam allowance near the notch. Press the seam allowance on the area from sleeve cap to mark and sew a decorative stitch along the seam at 0.5 cm. Press apart the seam allowances on the area from the mark down to hem and sew decorative stitch along the edges at 0.1 cm. Sew and press apart front sleeve seam. Sew a gathering stitch along a sleeve cap and gather fullness. Sew sleeves into armholes matching notches.
9. Fold cuffs in half lengthwise right sides together and sew short sides. Start and stop stitching exactly at the marked line of the cuff seam. Turn cuff right side out, straighten and press. Sew outer side of cuff to lower edge of sleeve, press towards cuff. Fold the seam allowance of the inner side onto the wrong side and press and topstitch into seam of.
10. Make buttonholes on right front, sew on buttons on the left one. Make buttonholes and sew on buttons onto cuffs and onto stand collar.

TECHNICAL DRAWING:

