

Longsleeve From Knit Fabric - Sewing Pattern #2619

Recommendations on fabric: soft natural/mixed knit fabric of medium stretchiness.

Seam allowances: all seams 1.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Inner front - cut 1 on fold
3. Outer front - cut 2
4. Front placket - cut 2
5. Sleeve - cut 2
6. Hem placket - cut 1 on fold
7. Cuff - cut 2

8. Back neck facing – cut 1

INSTRUCTIONS:

1. Serge the upper seam allowance of the inner front piece, turn inside and topstitch with two parallel stitch lines to prevent from stretching.
2. Pin together front placket in half lengthwise right side out and sew to the outer front piece. Press the seam allowance towards the main piece and serge.
3. Pin right front onto left front and baste together plackets along lower edge. Pin the outer front onto the inner front, and baste together along the armhole edges, along the side seam and along the lower edge.
4. Serge outer edge of back neckline facing. Pin neckline facing onto Back and sew neckline exactly up to the marked line of shoulder seam. Clip seam allowances, fold facing onto wrong side and press.
5. Sew shoulder seams, inserting the Front between the Back and the Facing, press towards the back and serge.
6. Sew side seams, press seam allowances towards back and serge.
7. Sew the hem placket into a ring, press the seam allowances apart. Pin together in half lengthwise right side out and sew to the lower edge of the garment. Press seam allowance towards top and serge.
8. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes, matching notches, serge and press.
9. Sew cuff into a ring, press the seam allowances apart. Fold cuff in half lengthwise right side out and sew to sleeve. Serge and press onto sleeve.

TECHNICAL DRAWING:

