

Skirt With Asymmetrical Pleats - Sewing Pattern #2658

Recommendations on fabric: natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing; dress zipper; 3 buttons.


Seam allowances: all seams 1 cm. Seam allowance for hem of garment - 1.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front skirt - cut 1
3. Back facing - cut 2
4. Front facing - cut 1

Fusible interfacing:

1. Back facing - cut 2

2. Front facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Serge center edges of the back skirt separately. Sew center seam from notch for zipper to hem. Press the seam apart. Sew in zipper.
3. Make and topstitch pleats on the front skirt according to the markings (the bulk is directed towards center).
4. Sew side seams, press towards the back and serge.
5. Sew side edges of facings, press the seam apart. Serge lower edge. Pin facing to skirt right sides together and sew upper edge. Topstitch seam allowances onto facing at 0.2 cm from the seam. Fold facing onto the wrong side, press. Slip stitch to the main piece along the side seams and zipper tape.
6. Serge lower edge of skirt, press onto wrong side and topstitch.
7. Sew on buttons at front skirt.

TECHNICAL DRAWING:

