

Short Wrap Blouse - Sewing Pattern #2678

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing; 1 button.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve - 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Sleeve - cut 2
4. Back neck facing - cut 1
5. Center front facing - cut 2
6. Belt - cut 2

Fusible interfacing:

1. Back neck facing - cut 1
2. Center front facing - cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew darts on back, press bulk towards center. Sew the center back seam, press towards left, serge.
3. Sew darts on front, shorten the bulk of the darts, press towards center and serge.
4. Fold belts in half lengthwise right sides together and sew along the shorter and the longer edge.
5. Sew shoulder and side seams, inserting a belt part into the left side seam. Press seams towards back, serge.
6. Sew side seams of back neckline facing and central front facings, press seam apart. Serge the outer edge. Pin the central front facings and the facings onto front, right sides together and sew center front facings and neckline, inserting the right belt. Clip into curves, turn the center front edges onto the right side, straighten, press. Topstitch the center front facings and the facing onto the garment.
7. Sew sleeve seam, press towards the back and serge. Sew sleeves into armholes matching notches, serge and press.
8. Press hem of garment and hem of sleeve onto wrong side at 1 cm, then again at 2 cm and topstitch.
9. On left front make a buttonhole, from the wrong side of right front sew on hidden button.

TECHNICAL DRAWING:

