

## Sewing Pattern — Dress 5956

Recommendations on fabric: natural or mixed fabric suitable for dresses.

You will also need: invisible zipper, fusible interfacing, lining

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem of the dress and hem of sleeve – 2.0 cm, along slit on back part – 2 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

#### Fabric:

1. Back - 2 details
2. Side front - 2 details
3. Central front – 1 detail
4. Yoke - 2 details
5. Sleeve - 2 details
6. Back facing - 2 details

#### Lining:

1. Yoke - 2 details (use main pattern pieces to cut)

Interfacing: back facing - 2 details, seam allowances along slit of back

### **INSTRUCTIONS:**

1. Apply interfacing to details.
2. Sew darts on back. Press darts toward center.
3. Serge middle edge of back. Sew middle seam from zipper mark down to slit. Press seam open, pressing the slit for zipper. Sew in zipper from top edge down to notch.
4. Sew middle edge of yoke and middle edge of lining from lower edge up to notch. Trim seam allowances near the notch and press open. Put yoke and lining right sides together and stitch on the neckline and front neckline edge to the notch. Clip seam on curves. Turn details out, straighten and press. Fasten yoke with lining on contour and further sew as one-layer detail.

5. Serge outer edge of the facings. Place facings on back facing right sides together. Leaving 5 mm to zipper edges, turn facing back and pin to top edge of the dress. Turn seam allowances along zipper to right side of the dress and pin to neckline edge on top of facing. Overstitch neckline edge. Clip seam on curves, turn details out and press. Turn seam allowances along zipper to wrong side and tack to zipper tape.
6. Sew shoulder seams of back and front, inserting yoke between back and facing. Serge seam, turn out and press toward back.
7. Sew central and side fronts, press seam toward center and serge. Stitch yoke to front. On central front trim seam in corner. Press seams downwards and serge. Sew side seams. Press seams to back and serge.
8. Sew edge of sleeve. Press and serge seam. Sew in sleeve into armhole, matching notches. Press and serge seam.
9. Press hem of the dress and hem of sleeve to wrong side, serge and slip-stitch. Slip-stitch sides of the slit.

**TECHNICAL DRAWING:**

