

## Jacket With Raglan Sleeves - Sewing Pattern #2784

Recommendations on fabric: natural/mixed knit fabric of small stretchiness.

You will also need: fusible interfacing; small raglan shoulder pads; separating zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve - 3 cm. Seam allowance along the slit of the sleeve - 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Back sleeve - cut 2
4. Front sleeve - cut 2
5. Center front facing - cut 2
6. Back neck facing - cut 2

Fusible interfacing:

1. Center front facing - cut 2
2. Back neck facing - cut 2

## **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew darts on front, press bulk towards top.
3. Sew the center back seam, press seam allowances towards left, serge.
4. Sew the back sleeves to the back, press seam allowances towards sleeve, serge. Sew front sleeves to front, press seam allowances towards sleeve, serge.
5. Serge the upper edges of the sleeves separately. Sew the upper sleeve seam from the upper edge up to the mark, press the seam apart. Sew lower edges of sleeves and side edges continuously, press towards the back, serge. Sew on shoulder pads.
6. Sew center seam of back neckline facing, press the seam apart. Sew shoulder seams of central front facings and facings, press the seam apart. Serge the outer edge.
7. Pin the center front facings and the facing onto the garment, right sides together, and sew along the center front edge, the stand collar edge and the lower edges, inserting the zipper in between the pieces.
8. Serge seam allowance for hem of garment and hem of sleeve, press onto wrong side and finish with hidden stitches. Hem the seam allowances of the sleeve slit with invisible stitches.

## **TECHNICAL DRAWING:**

