

## Sweatshirt With Pocket - Sewing Pattern #2785

Recommendations on fabric: thick natural/mixed knit fabric of small stretchiness (fleece, fleece). Knit braid.

Seam allowances: all seams 1 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

### Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 – 0.8 cm.



## CUTTING:

### Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Front – cut 1 on fold
2. Front side – cut 1 on fold
3. Back – cut 1 on fold
4. Inset – cut 2
5. Front sleeve – cut 2

6. Back sleeve - cut 2
7. Pocket - cut 1

Main fabric 2:

1. Lower placket - cut 1 on fold
2. Cuff - cut 2
3. Collar - cut 1

## **INSTRUCTIONS:**

1. Pin pocket onto front right side down and sew the pocket opening from the bottom up to the marked line of the pocket seam. Fold away pocket onto wrong side. Sew the fastening stitch lines along the pocket opening from the top down to the lower arrow mark. Snip into seam allowance in the corner on side front. Pin the front onto the side front, match edges. Sew and serge the upper edge of pocket. Sew side front to front. Serge seams and press towards center. Sew a decorative stitch line along the princess seam from the top down to the upper arrow mark. Topstitch the pocket area onto the side piece from the lower mark down to the bottom. Sew the fastening perpendicular stitches near the arrow marks.

2. Sew Front Sleeve to Front. Serge, press onto front and sew a decorative stitch at 0.5 from seam. Sew Back Sleeve to Back. Serge, press towards back and sew a decorative stitch at 0.5 from seam. Sew inset to front and to back. Serge the seam allowances and press towards inset. Sew a decorative stitchline.

3. Sew collar into a ring. Pin together in half lengthwise and sew into neckline, slightly stretching it collar. The seam is located near the left shoulder seam. Serge and press towards the main piece.

Sew side seams and sleeve seams continuously. Serge seams and press towards back.

4. Sew cuff into a ring. Press the seam apart. Fold cuff in half lengthwise. Sew cuff to lower edge of sleeve, slightly stretching the cuff.

5. Sew placket into ring. Pin together in half lengthwise and sew to the lower edge of the garment, slightly stretching the placket. The seam is placed near the left side seam. Serge.

## **TECHNICAL DRAWING:**

