

Summer Jacket - Sewing Pattern #2805

Recommendations on fabric: natural/mixed suiting fabrics.

You will also need: fusible interfacing; two buttons.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment - 2.5 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Back yoke - cut 1
3. Front - cut 2
4. Sleeve - cut 2
5. Cuff - cut 2
6. Center front facing — cut 2
7. Back neck facing — cut 1

8. Decorative Tab – cut 2

Fusible interfacing:

1. Cuff – cut 2
2. Center front facing — cut 2
3. Back neck facing — cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew yoke to back. Serge seams and press towards top.
3. Sew center edge of one-piece collar. Clip into seam allowance of shoulder seam in the corner. Sew shoulder seams, sewing collar into the neckline at the same time. Clip seam allowances and press.
4. Sew the center collar edge on center front facings. Press the seam allowances apart. Sew shoulder seams facings and center front facings, sewing collar into the neckline at the same time. Serge the outer edge. Pin center front facing to garment right sides together and sew along the center front edge and of collar. Clip seam allowances, trim away corners, fold away center front facings onto wrong side and press.
5. Fold decorative tabs in half lengthwise right sides together and sew along longer and one shorter edge. Turn right side out, snipping the seam allowances in corners, straighten and press. Serge the unfinished shorter edge. Make buttonhole on tab. Topstitch decorative tabs according to the markings onto the wrong side of sleeves.
6. Sew sleeves into armholes. Serge the seam allowances and press onto sleeve.
7. Sew side seams, sewing the sleeve edges at the same time. Serge seams and press towards back.
8. Sew cuff into a ring. Fold cuff in half lengthwise right side out and press. Sew the outer part of the cuff to the sleeve, fold inside the inner side of the cuff, and topstitch into the seam of the outer cuff cuffs.
9. Serge the lower edge of garment. Press onto wrong side and topstitch.
10. Make buttonholes on decorative tabs. Sew on buttons on sleeves.

TECHNICAL DRAWING:

