

Cape With Belt - Sewing Pattern #2810

Recommendations on fabric: thin woolen fabrics.

You will also need: lining; fusible interfacing; 1 button.

Seam allowances: all seams 1.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1
2. Front - cut 2
3. Collar - cut 2
4. Center front facing - cut 2
5. Back neck facing - cut 1
6. Belt - cut 1 on fold

Lining:

1. Back - cut 1
2. Front - cut 2

Attention: front pieces and back pieces from lining are cut using the pattern pieces for the main fabric except for the width of the center front facings and of the back neckline facing correspondingly.

Fusible interfacing:

1. Collar - cut 1
2. Center front facing - cut 2
3. Back neck facing - cut 1
4. Belt - cut 1 on fold

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Pin collar, right sides together, and sew ends and outer edge. Trim away corners, turn collar right side out, straighten and press.
3. Sew shoulder seams, press the seam apart.
4. Sew side seams of center front facings and back neckline facings, press the seam apart. Pin the center front facings to the garment, right sides together, insert the collar in between and sew along the center front edge and along the neckline. Clip into curves, turn the center front facings onto wrong side, straighten, press.
5. Sew the shoulder edges on lining, press the seam apart. Sew lining to the central front facings and to facing. Sew the lower edge of the garment between the marks. Clip into curves, turn garment right side out, straighten and press.
6. Fold belt in half lengthwise right sides together and sew the ends and the area between the marks. Clip into seam allowances near notches, turn belt right side out, straighten, press.
7. Sew the outer side of the belt to the garment, fold under the seam allowance of the inner side and stitch-in-the-ditch along seam of outer side.
8. Make a buttonhole on the right side of the belt, sew on a button on the left side.

TECHNICAL DRAWING:

