

## Sewing Pattern — Dress 5945

Recommendations on fabric: double-sided knitted fabric of low or medium stretchiness. For collar thinner knit fabric can be used, but double-sided.

You will also need: fusing for collar

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: hem, lower edge of sleeve and top edge of collar – 1.5 cm, all other seams - 0.8 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

#### Main fabric:

1. Back part – 1 detail on fold
2. Front part – 1 detail on fold
3. Sleeve – 2 details
4. Collar – 1 detail

#### Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Sew shoulder seams, serge and press towards back part.
2. Sew sleeve into open armhole. Serge the seam and press it to the sleeve.
3. Sew edge of sleeve, continuing to side seam. Serge the seam and press it towards back part.
4. Sew collar into ring. Serge and press the seam. Sew collar into the neckline, placing seam of collar near left shoulder seam. Serge and press the seam.
5. Serge hem of garment, upper edge of collar and lower edge of sleeve. Turn onto wrong side, press and topstitch.



**TECHNICAL DRAWING:**

