

## Sewing Pattern — Dress 5942

Recommendations on fabric: knit fabric of middle stretchiness of natural or mixed fibers

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance : on hem and sleeve hem – 2 cm, all other seams 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Upper back part – 2 details
2. Lower back part – 1 detail
3. Lower front part – 1 detail
4. Upper front part – 2 details
5. Middle part of front part – 2 details
6. Collar – 2 details
7. Sleeve – 2 details

#### Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

### **INSTRUCTIONS:**

1. Sew darts on top parts of front part, press depths towards details' center.
2. Sew top and middle parts of front part, press seam onto middle part and serge.
3. Sew middle edge of back part, press seam onto left side and serge. Sew shoulder seams, press seam onto back part and serge.
4. Sew details of collar together. Press collar in half lengthwise wrong sides together. Stitch collar to middle edge of front part and neckline of the garment, press seam allowances and serge. Put right side of collar on left, and fix details near seam cut.
5. Stitch corresponding lower details to top parts of back and front parts, press seam allowances downwards and serge.

6. Sew side seams. Press seam allowances towards back part and serge.
7. Sew edges of sleeve. Press seam allowances and serge.
8. Sew sleeves in armholes, aligning notches. Press seam allowances and serge.
9. Serge hem of garment and lower edge of sleeve. Turn onto wrong side, press and topstitch.

**TECHNICAL DRAWING:**

