

Blouse With Decorative Stand Collar - Sewing Pattern #2842

Recommendations on fabric: natural/mixed fabrics suitable for blouses in contrasting colors.

You will also need: fusible interfacing.

Seam allowances: all seams 1 cm. Seam allowance along the lower edge of the garment - 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 1 on fold
2. Front - cut 2

Main fabric 1:

1. Front inset - cut 2

Fusible interfacing:

1. Front inset - cut 1

INSTRUCTIONS:

1. Apply fusible interfacing to inset.
2. Sew center seam on front, press towards left, serge. Sew the outer front inset to front, press the seam allowances towards inset.
3. Serge the outer edge of the inner inset. Pin insets right sides together and sew the neckline. Clip seam allowances, turn the inner inset to the wrong side. Topstitch into the seam of the outer stand collar.
4. Sew shoulder seams, slashing front in the corner. Press seams towards back and serge.
5. Sew the seam of the stand collar, pinning pieces right sides together, press the seam apart. Form the stand collar, folding the piece along the marked line. Sew the outer side into the neckline, clip seam allowances and press towards stand collar. Fold under the seam allowance of the inner stand collar and topstitch into the seam of the outer stand collar.
6. Cut or use ready-made bias tape, its width should equal 4 cm and length should equal the length of armhole + 5 cm. Fold bias tape in half lengthwise right side out and press. Pin bias tape onto armhole edge from the right side and sew. Clip into seam allowances. Fold bias tape onto wrong side and topstitch onto main piece along the seam. Press seam.
7. Sew side seams, press towards the back and serge.
8. Serge hem of garment, press onto wrong side and topstitch.

TECHNICAL DRAWING:

