

## Short Coat With One Button - Sewing Pattern #2854

Recommendations on fabric: thin natural/mixed fabric suitable for coats.

You will also need: fusible interfacing; lining; shoulder pads; 3 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of sleeve – 3 cm.

### Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

### Note on length of fabric:

*Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.*



## CUTTING:

### Note on cutting:

*On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.*

*When sewing the garment, pay attention to notches, they must match up.*

Main fabric:

1. Back – cut 2
2. Front – cut 2
3. Front yoke – cut 2
4. Upper sleeve – cut 2
5. Lower sleeve – cut 2
6. Center front facing — cut 2

7. Back neck facing – cut 1
8. Back hem facing – cut 1
9. Flap – cut 4

Lining:

1. Back – cut 2
2. Front lining – cut 2
3. Upper sleeve – cut 2
4. Lower sleeve – cut 2

Attention: back pieces from lining are cut using the pattern piece for the main fabric EXCEPT for the width of the back neckline facing and the back hem facing.

Fusible interfacing:

1. Front – cut 2
2. Front yoke – cut 2
3. Center front facing — cut 2
4. Back neck facing – cut 1
5. Back hem facing – cut 1
6. Flap – cut 2

## **INSTRUCTIONS:**

1. Apply fusible interfacing.
2. Sew shoulder and waist darts on backs, press bulk towards center. Sew the center back seam, press the seam apart.
3. Sew front darts, cut away the bulk of the dart leaving 1 cm, press towards center.
4. Sew flaps together by two, right sides together and sew the side and the lower edges. Trim seam allowances, turn the flap right side out, straighten, press. Make a buttonhole.
5. Sew yoke to front, inserting according to markings flap. Seam Allowances press onto yoke.
6. Sew side and shoulder seams, clipping into corners on front, press the seam apart.
7. Sew center edge of one-piece collar, press the seam apart. Sew collar into neckline, press the seam apart.
8. Sew shoulder edges of center front facings and back neckline facing, press the seam apart. Sew back hem facing to the central front facings, press the seam apart. Sew center collar seam, press the seam apart. Sew

the collar into the facing's neckline, clipping into seam allowance near corner, press the seam apart.

9. Pin center front facing onto main piece, right sides together and sew around center front edge, collar and lower edge. Topstitch seam allowance of the central front facing onto the central front facing. Place stitch line at 0,2 cm from seam. Turn center front facing onto wrong side, straighten, press. Slip stitch together seam allowances along collar seams.

10. Sew the elbow seam, press apart. Press the hem of sleeve. Sew the front sleeve seam, press apart. Sew sleeves into armholes matching notches. Sew shoulder pads.

11. Sew together pieces of lining in the same way as you have sewn pieces from main fabric, leaving an opening in left elbow seam of sleeve. Sew lining to facings. Turn garment right side out, straighten seams.

12. Mark the hem, fold inside and press. Sew lining to the hem of the garment and to the hem of the sleeve. Sew the opening closed.

13. Make buttonhole on right front, on left front sew on a button. Sew on buttons according to the button loops on the flaps.

## **TECHNICAL DRAWING:**

