

Dress With Exposed Seams - Sewing Pattern #2864

Recommendations on fabric: non-fraying knit fabric with low stretch made of natural or blended fibers.

You will also need: knit fusible interfacing.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment - 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke - cut 1 on fold
2. Center back upper - cut 1 on fold
3. Center back lower - cut 1 on fold
4. Side back - cut 2
5. Front yoke - cut 1 on fold
6. Center front upper - cut 1 on fold
7. Center front lower - cut 1 on fold

8. Middle front - cut 2
9. Side front - cut 2
10. Sleeve - cut 2
11. Cuff - cut 2
12. Stand collar - cut 1

Fusible interfacing:

1. Cuff - cut 2
2. Stand collar - cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Place the upper and lower center back pieces with wrong sides facing and sew. Press seam. Sew side backs to center back, the pieces should be pinned together wrong sides together. Press seam. Sew yoke to back, the pieces should be pinned together wrong sides together. Press seam.
3. Place the upper and lower center front pieces with wrong sides facing and sew. Press seam. Sew side fronts to front, the pieces should be pinned together wrong sides together. Press seam. Sew yoke to front, the pieces should be pinned together wrong sides together. Press seam.
4. Sew shoulder seams, press towards the back and serge.
5. Sew stand collar into a ring, press the seam apart. Pin together stand collar in half lengthwise right side out and press. Sew stand collar, slightly stretching it, into neckline, press seam allowances towards the garment, serge and topstitch along the seam onto the main piece.
6. Sew the sleeve to the garment, the pieces should be pinned together wrong sides together. Press seam.
7. Sew the sleeve edges and side seams in one seam, press towards the back, serge.
8. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, slightly stretching it, press towards top and serge.
9. Serge lower edge of garment, press onto wrong side and topstitch.

Tip: Ready-made rib knit collar stand and cuffs of the required width may be used.

TECHNICAL DRAWING:

