

Knit Sweatshirt With Decorative Yoke - Sewing Pattern #2866

Recommendations on fabric: natural/mixed knit fabric of small stretchiness. Rib knit fabric for cuffs, waistband, and stand collar.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.

Note on working with stretchy fabric:

Knitted fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hems can be stitched with twin needles to save stretchiness. Pieces can also be sewn together with a serger. When serging, cut seam allowances to 0.6 - 0.8 cm.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back yoke - cut 1 on fold
2. Back - cut 1 on fold
3. Front yoke - cut 1 on fold
4. Front - cut 1 on fold
5. Upper sleeve - cut 2

6. Lower sleeve - cut 2

Knit band:

1. Cuff - cut 2
2. Stand collar - cut 1
3. Belt - cut 1 on fold

INSTRUCTIONS:

1. Sew yoke to front, pinning pieces right sides together. Seam Allowances press onto yoke and topstitch at 0.5 cm from seam.
2. Sew shoulder seams, press towards the back and serge.
3. Sew stand collar into a ring, press the seam apart. Pin together stand collar in half lengthwise right side out and press. Sew stand collar, slightly stretching it, into neckline, press seam allowances towards stand collar, serge.
4. Sew upper sleeve to lower sleeve, press seam allowances at lower part, serge and topstitch at 0.5 cm from seam. Sew the sleeve to the garment, pinning pieces right sides together. Press towards sleeve, serge.
5. Sew the sleeve edges and side seams in one seam, press towards the back, serge.
6. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew cuff to lower edge of sleeve, slightly stretching it, press seam allowances towards sleeve and serge.
7. Sew waistband into a ring, press the seam apart. Fold belt in half lengthwise right side out and press. Sew the waistband to the lower edge of the garment, slightly stretching it; press the seam allowances upward and serge.

Tip: it is possible to use ready-made stand collar, waistband, and cuffs of the required width.

TECHNICAL DRAWING:

