

Leather Jacket - Sewing Pattern #2871

Recommendations on fabric: eco leather or natural leather.

You will also need: lining; 1 separating zipper (approximate length is given on the front pattern piece); 2 zippers for pockets; 2 push buttons; 2 decorative push buttons; shoulder pads.

Seam allowances: all seams 1 cm, Seam allowances at the hem of the back, side panel, and side front - 3 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Center front right - cut 1
4. Center front left - cut 1
5. Side front - cut 2
6. Front yoke - cut 2
7. Front side - cut 2

8. Stand collar - cut 2
9. Back yoke — cut 2
10. Upper sleeve - cut 2
11. Lower sleeve - cut 2
12. Sleeve inset — cut 2
13. Lower sleeve inset — cut 2
14. Back neck facing - cut 1
15. Center front facing right - cut 1
16. Center front facing left - cut 1
17. Underlay piece - cut 2
18. Sleeve placket — cut 2

Lining:

1. Center back - cut 2
2. Center front - cut 2
3. Side back - cut 2
4. Side front - cut 2
5. Upper sleeve - cut 2
6. Lower sleeve - cut 2
7. Bigger pocket bag — cut 2
8. Smaller pocket bag — cut 2

Attention! Pattern blocks have markings and texts from the right side. Take this into account when cutting the fabric-some of the pattern blocks need to be laid onto fabric with their wrong side on top!

INSTRUCTIONS:

1. Sew side backs to center back. Press the seam apart. Topstitch on both sides of the seam at 0.2 cm. Sew center back seam. Topstitch the seam allowances in the same way.
2. Sew back yoke to yoke. Press seam allowance towards top and topstitch at 0.2 cm from seam.
3. Sew the front side panel to the side front. Start and stop stitching exactly at the marked line of pocket. On the side panel, clip the seam allowances at the pocket markings, press the princess seam allowances toward the center, press the pocket opening.
4. Topstitch underlay piece onto bigger pocket bag of pocket. Mark the position of pocket on front. Snip diagonally toward end of stitching at 1-1.5 cm from end of pocket opening (on the side front). Fold seam allowances of the pocket under through the resulting opening, straighten the edges. Sew the pocket bags right sides to the wrong side of the zipper tape. Place the zipper under the edges of the pocket opening so that the teeth are visible. Sew in the zipper, stitching from the right side and folding back the pocket bags. Sew the edges of the pocket bags, catching the corners.

5. Topstitch along the princess seam at 0.2 cm from the seam, starting and ending at the pocket opening.
6. Sew the right side front to the front. Press the seam allowances away from the center. Sew a decorative stitch at 0.2 cm from seam. Sew the left side front to the front, inserting the zipper. Press the seam allowances away from the center. Sew a decorative stitch at 0.2 cm from seam.
7. Sew yoke to front. Press seam towards yoke and sew a decorative stitch at 0.2 cm from seam.
8. Sew the shoulder edges and the side edges, press the seam apart of jacket.
9. Sew together the upper sleeve, insert, and lower sleeve insert. Press the seam allowances toward the insert and sew a decorative stitchline at 0.2 cm from the seams. Sew elbow seam on the sleeve up to notch, marking the slit. Clip the seam allowance on the lower sleeve at the notch level. Press the seam allowance toward the upper sleeve and topstitch along the elbow seam at 0.2 cm from the seam. Sew front sleeve seam. Set the sleeves into the jacket. Sew on shoulder pads.
10. Pin together stand collars right sides together and sew along the outer edges. Trim away corners, turn right side out and press. Topstitch along the outer edges.
11. Sew shoulder seams of central front facings and facings. Press the seam apart. Sew seams on lining, leaving an opening in left side seam. Sew in the sleeves.
12. Sew the zipper to the right front edge (zipper blade should be faced away from the center front edge). Place center front facing onto front right sides together and sew lower edge center front facings, along the center front edge, neckline, inserting collar. Clip into curves, turn right side out and press. Press lower seam allowances. Sew lining to the central front facings and to facing. Sew the lower edge of the lining to the hem of the garment. Press the seam apart.
13. Sew the lining to the sleeve seam allowances along the slit. Secure the lower edges of the sleeve and lining at 0.5 cm from the edge. Fold cuff in half lengthwise, right sides together. Stitch the step and the short side. Trim seam allowances and turn the piece right side out. Turn Under seam allowances inside and press. Sew the cuff edges, inserting the sleeve between them. Topstitch the cuff along the contour, continuing the seam that attaches the cuff to the sleeve.
14. Sew a decorative stitchline around all edges stand collars.
15. Sew an additional decorative stitch along center front edge at 0.5 cm from zipper. Topstitch along the hem of the side fronts and back. Attach snap fasteners to the cuffs. Attach decorative snap fasteners to the lapels.

TECHNICAL DRAWING:

