

Blouse With Yoke And Pleated Stand Collar - Sewing Pattern #2880

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing, dress zipper.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment and hem of sleeve - 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 1 on fold
3. Yoke - cut 2
4. Sleeve - cut 2
5. Center front facing - cut 2
6. Back neck facing - cut 2

Fusible interfacing:

1. Center front facing – cut 2
2. Back neck facing – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew darts on back and front, press the bulk of waist darts towards center, press bulk of bust darts towards top.
3. Serge the inner edge of center front facing. Pin the front facing and the front yoke right sides together and sew the outer edge. Clip into curves, turn the piece right side out, press. Pin right yoke onto left yoke, baste together along lower edge. Sew yoke to front, press towards top and serge.
4. Stitch the shoulder seams, folding back the front facing and clipping the shoulder seam allowance on the yoke, press towards the back and serge. Sew the stand collar into the back neckline, press seam allowances towards stand collar.
5. Serge the center back edges separately. Sew the center back seam from notch to bottom, press the seam apart. Sew the zipper, starting from the upper edge of the stand collar.
6. Serge outer edge of back neckline facing. Sew shoulder seams of back neckline facing and center front facings, clipping into corners on center front facing, press the seam apart. Sew the stand collar into neckline facings, press seam allowances towards stand collar. Fold the center edge of the inner stand collar to the inside and sew it by hand to the zipper tape. Slip stitch the shoulder seams of the center front facings to the shoulder seams of the garment.
7. Sew side seams, press towards the back and serge.
8. Sew sleeve seam, serge and press. Sew sleeves into armholes, serge and press.
9. Serge the hem of the garment and the hem of the sleeves, press onto wrong side and topstitch.

TECHNICAL DRAWING:

