

## Sewing Pattern — Gathered Roll-Neck 5930

Recommended fabric: middle/high stretch-knit jersey (natural or mixed).

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 1.5 cm for the garment and sleeve hems, 1 cm for other seams.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### **Advice:**

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

### **Main fabric:**

1. Center front – cut 1
2. Back – cut 1
3. Side front – cut 2
3. Sleeve – cut 2
4. Collar – cut 1

**\*Note:** Make sure your fabric is stretchy enough so that collar will fit over your head. We suggest trying collar length of fabric first, then adjusting it to fit.

**INSTRUCTIONS:**

1. Make a gathering stitch along both sides of center front curved edges and gather. Sew side front to center front curved edges, matching notches. Serge and press seam toward sides.
2. Sew shoulder seams. Serge, and press seam toward back.
3. Sew sleeves into open arm-holes, matching notches. Serge and press seam toward sleeve. Sew side seam and sleeve seam with one stitch. Serge and press seam toward back.
4. Fold the collar piece in half, right side out. Sew the collar to the neckline, matching notches. Collar side seam is at the left shoulder seam. Serge and press seam toward garment.
5. Serge lower edge of sleeves and garment. Turn onto wrong side, press, and topstitch.

**TECHNICAL DRAWING:**