

Sewing Pattern — Dress 5929

Recommendations on fabric: knitted fabric of natural or mixed fibers.

You will also need: fusing

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem and hem of sleeve – 2 cm, on neckline edge of back part and of front part – 1.5 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 details
2. Front part – 1 folded detail
3. Panel of front part – 4 details
4. Sleeve – 2 details

Fusing:

1. Panel of front part – 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Apply fusing to panels of front part.
2. Serge upper edge of front part, press onto wrong side and topstitch. Make plaits and fasten according to markers.
3. Fold panels of front part wrong sides inwards, insert detail of front part between them and sew. Turn panels right side out, press. Next sew panels as one-layer.

4. Sew middle edge of back part. Press seam allowances on left side and serge.
5. Sew shoulder seams. Attention: shoulder edge of back part is longer than shoulder edge of front part on 1.5 cm (seam allowance for sewing back part neckline). Press seam towards side of back part.
6. Sew side seams. Press seam allowances towards back part and serge.
7. Sew edges of sleeve. Press seam allowances and serge.
8. Sew sleeves into armholes, coinciding notches. Press seam allowances and serge.
9. Serge hem of garment, lower edge of sleeve and edge neckline of back part. Turn onto wrong side, press and topstitch.

TECHNICAL DRAWING:

