

## Sewing Pattern — 6 Gore Skirt 5924

Recommendations on fabric: well draping, natural or mixed fabrics

You will also need: fusible interfacing, 1 zipper, 1 button

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem - 2 cm; all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Fabric:

1. Center panel - cut 2
2. Side panel - cut 4
3. Waistband – cut 1

Fusible interfacing: waistband

### **INSTRUCTIONS:**

1. Apply interfacing to waistband.
2. Sew side panels to front and back panels of the skirt, serge and press seams toward center.
3. Sew right side seam. Serge and press toward back. Sew left side edges separately. Sew left side seam from zipper mark to hem. Press seam apart, including opening for zipper. Sew in zipper.
4. Sew outer waistband edge to top edge of the skirt, right sides together. Left end should extend slightly for button. Fold waistband in half and sew ends. Trim corners and turn right side out. Turn inner edge of waistband under, and topstitch into connecting seam. Press.
5. Serge bottom edge of skirt, press onto wrong side, and topstitch.
6. Mark and make buttonhole. Sew the button.

**TECHNICAL DRAWING:**

