

Sleeveless Blouse With Ruffles - Sewing Pattern #2924

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing; 4 buttons.

Seam allowances: all seams 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Side front - cut 2
4. Center front - cut 2
5. Center front facing - cut 2
6. Stand collar — cut 2

7. Armhole ruffle – cut 2
8. Hem ruche — cut 2
9. Collar stand ruffle — cut 1
10. Back neck facing – cut 1

Fusible interfacing:

1. Stand collar — cut 1
2. Center front facing – cut 2
3. Back neck facing – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew side backs to center back, press seam allowances towards center, serge.
3. Sew the center back seam, press towards left, serge.
4. Sew side front to center front, press seam allowances towards center, serge.
5. Sew shoulder seams, press seam allowances towards back and serge.
6. Serge the outer edge and the short edges of the collar stand ruffle, press onto wrong side and topstitch. (You may also finish them with baby hem, in this case trim away seam allowance). Sew a row of gathering stitches along the inner edge of the ruffle with reduced upper thread tension and gather fullness. Pin stand collars together, right sides together, insert the ruche in between and sew, sewing the ends of stand collar at the same time. Turn the finished stand collar right side out and press. Sew the stand collar into neckline.
7. Serge the outer edges of the armhole ruffle, press onto wrong side and topstitch. (You may also finish them with baby hem, in this case trim away seam allowance). Sew a row of gathering stitches along the inner edge of the ruffle with reduced upper thread tension and gather fullness. Sew the ruffle to the armhole, press towards the main piece and serge. Sew a fixing stitch at 0.5 cm from seam.
8. Sew side seams, press seam allowances towards back and serge.
9. Sew shoulder seams of back neckline facing and center front facings, press the seam apart. Serge the outer edge. Place the center front facings on the right side of the garment and stitch the center front edges and the back and front necklines. Clip the seam allowances, turn the facing with the center front facings to the wrong side, and press. Sew the facing to the seam allowances of the shoulder seams by hand.
10. Stitch the bottom ruffle pieces together. Press the seam allowances open and serge them. Serge the outer edge and the short edges of the bottom ruffle, press them to the wrong side, and topstitch. (You may also finish

them with baby hem, in this case trim away seam allowance). Sew a row of gathering stitches along the inner edge of the ruffle with reduced upper thread tension and gather fullness. Sew the bottom ruffle to the bottom edge of the garment, press towards the main piece and serge. Sew a fixing stitch at 0.5 cm from seam.

11. Make buttonholes on right front, sew on buttons on the left one.

TECHNICAL DRAWING:

