

Sewing Pattern — Skirt 5923

Recommendations on fabric: natural or mixed thin costume fabric

You will also need: lining, fusing; 1 blind zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm; hem of the garment and of lining - 2 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

Lining details are cut using main fabric pattern pieces and are 2 cm shorter than main length.

CUTTING:

Main fabric:

1. Back panel – 2 details
2. Yoke of back panel – 2 details
3. Central part of front panel – 1 detail
4. Side part of front panel – 2 details
5. Yoke of front panel – 2 details

Lining:

1. Back panel – 2 details
2. Central part of front panel – 1 detail
3. Side part of front panel – 2 details

Fusing:

1. Yoke of back panel – 1 detail
2. Yoke of front panel – 1 detail



INSTRUCTIONS:

1. Apply fusing to yokes and to seam allowances of the vents.
2. Serge center edges of back panel separately on each detail, serging the vent at the same time. Sew center edge from the top up to the edge of the vent. Press seam allowances apart, press seam allowances of the vent to left side edge. Press right side of the vent at 1 cm and topstitch. Fix seam allowances of the vent with machine stitch.
3. Stitch loosely on longitudinal edges of front panel's central part from the top up to the notch and gather ruffles. Stitch side parts of front panel to central part, press seam allowances to side edges and serge.
4. Stitch yokes to corresponding parts, press seam allowances upwards and serge.
5. Serge separately left side edges of back and front panels. Sew left side edge from zipper marker downwards. Press apart seam allowances and press slits for zipper. Sew zipper into left side seam of the skirt. Sew, press towards back part and serge right side seam.
6. Sew right side seam on details of inner yokes, press seam allowances apart. Cut off seam allowance of the vent on lining details of back panel and sew center edge. Press seam allowances onto left side and serge. Sew edges on details of lining the same way as on main fabric details. Stitch lining to inner yokes, press seam allowances upwards. Fold inner yokes with the skirt right sides together and overstitch upper edge, slash seam allowances on rounded parts. Turn the skirt right side out. Stitch seam allowances that are for zipper to zipper tape. Fix lining to the garment, topstitching it into connecting seam of outer yokes.
7. Serge lower edge of the skirt, press onto wrong side and topstitch. Turn the skirt wrong side out, straighten, align corresponding seams on main garment and on lining. Cut lining carefully as half circle above the vent, serge the edge. Turn hem of lining twice inside and topstitch.

TECHNICAL DRAWING:

