

Blouse With A Shaped Stand Collar - Sewing Pattern #2928

Recommendations on fabric: thick natural/mixed fabric suitable for dresses.

You will also need: fusible interfacing; dress zipper.

Seam allowances: all seams 1 cm; seam allowance for hem of garment – 2.0 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Front - cut 1 on fold
3. Sleeve - cut 2
4. Cuff – cut 2
5. Stand collar – cut 4

Fusible interfacing:

1. Cuff – cut 2
2. Stand collar – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew darts on front, press bulk towards top.
3. Sew shoulder seams, press towards the back and serge.
4. Serge the lower edges of the inner collar stands. Place the collar stand pieces in pairs, right sides together, and stitch along the upper and front edges (start or stop stitching exactly at the marked collar attachment line). Clip seam allowances, trim away corners, turn right side out stand collars onto right side, straighten, press.
5. Sew outer stand collars into neckline, press seam allowances towards stand collars.
6. Serge the center back edges separately. Sew the center back seam from zipper mark to hem, press the seam apart. Sew in zipper starting from the upper edge of the stand collar, folding the inner stand collar away. Fold inside the shorter seam allowances of the inner stand collar and sew them to the zipper tape. Topstitch the inner collar in the seam of the outer collar.
7. Sew side seams, press towards the back and serge.
8. Sew sleeve seam, press towards the back and serge.
9. Sew sleeves into armholes, matching notches, serge and press.
10. Sew cuff into a ring, press the seam apart. Fold cuff in half lengthwise right side out and press. Sew outer side of cuff to lower edge of sleeve, press seam allowances towards sleeve. Fold the seam allowance of the inner cuff inward and stitch in the seam attaching the outer cuff.
11. Seam allowance for hem of garment press towards 1 cm onto wrong side, then again at 1 cm and topstitch.

TECHNICAL DRAWING:

