

Wrap Blouse - Sewing Pattern #2941

Recommendations on fabric: natural/mixed fabrics suitable for blouses.

You will also need: fusible interfacing; 1 button; 1 inner button.

Seam allowances: all seams 1 cm; seam allowance for hem of garment – 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back - cut 2
2. Right front - cut 1
3. Left front - cut 1
4. Sleeve - cut 2
5. Back neck facing - cut 1
6. Center front facing of right front - cut 1
7. Center front facing of left front - cut 1

Fusible interfacing:

1. Back neck facing — cut 1
2. Center front facing of right front – cut 1
3. Center front facing of left front – cut 1

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew the center back seam, press towards left, serge. Sew waist darts, press bulk towards center.
3. Sew front darts, press bulk towards top. Sew waist darts, press bulk towards center.
4. Sew shoulder seams, press seam allowances towards back, serge.
5. Cut a fabric strip 4 cm wide and 90–100 cm long. Fold the strip in half lengthwise, wrong sides together, and press. Fold the long edges inward and press. Stitch to secure. Cut the cord into two equal lengths.
6. Stitch the side seams, inserting one piece of cord into the left side seam. Press seam allowances towards back, serge.
7. Sew shoulder edges of center front facings and back neckline facing, press the seam apart. Serge the outer edge. Place the center front facings and the garment right sides together and stitch the back neckline and front edges, inserting the second piece of cord into the right front edge. Clip into curves, trim away corners, turn the center front facings onto wrong side, straighten, press. Topstitch along the front edges and back neckline 0.5 cm from the edge.
8. Sew sleeve seam, serge and press. Sew a gathering stitch along the sleeve cap and gather fullness. Sew sleeves into armholes, serge and press.
9. Serge hem of garment and hem of sleeve, press onto wrong side and topstitch.
10. Make buttonhole on right front, sew on buttons on the left one. Make the inner button hole on left front. Sew on the inner button opposite the corresponding buttonhole.

TECHNICAL DRAWING:

