

Blouse With Decorative Tie - Sewing Pattern #2891

Recommendations on fabric: blouse fabrics, thin natural/mixed jeans fabrics.

You will also need: fusible interfacing, 7 buttons.

Seam allowances: all seams 1 cm. Seam allowance for hem of garment – 2 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Note on cutting:

On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.

When sewing the garment, pay attention to notches, they must match up.

Main fabric:

1. Back – cut 1 on fold
2. Back yoke – cut 1 on fold
3. Front – cut 2
4. Front yoke – cut 2
5. Sleeve – cut 2
6. Collar – cut 2
7. Stand collar – cut 2

8. Placket – cut 4
9. Cuff – cut 2

Fusible interfacing:

1. Collar – cut 1
2. Stand collar – cut 1
3. Placket – cut 2
4. Cuff – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing.
2. Sew back yoke to back. Serge the seam allowances, press towards top. Sew a decorative stitch at 0.5 cm from seam.
3. Sew a gathering stitch along upper edge of front and gather fullness. Sew yoke to front. Serge the seam allowances and press towards top. Sew a decorative stitch at 0.5 cm from seam.
4. Cut a fabric strip 4 cm wide and 90–100 cm long. Fold the strip in half lengthwise, wrong sides together, and press. Fold the long edges inward and press. Stitch to secure. Cut the cord into two equal lengths.
5. Pin plackets together, right sides together and sew the outer edge, clip seam allowances, turn right side out, straighten, press. Sew the outer placket to the right side of the front piece, inserting ties according to markings. Fold inside seam allowance of inner placket and topstitch from the right side at 0.2 cm from the edge. Sew a decorative stitch at 0.2 cm from the edge center front facings.
6. Sew side and shoulder seams, press towards the back and serge.
7. Pin collars together, right sides together, and sew the ends and the outer edge of collar. Trim away corners. Turn the collar right side out, straighten and press. Sew a decorative stitch at 0.5 cm from fold. Pin stand collars together right sides together, insert the ready collar between them and sew, sewing the ends of stand collar at the same time. Start and stop stitching exactly at the marked stitchline of collar. Clip into seam allowances on curves. Turn finished collar right side out and press.
8. Sew upper stand collar into neckline, fold raw edge of lower stand collar and stitch-in-the-ditch along seam of upper stand collar.
9. Sew a gathering stitch along a sleeve cap and gather fullness. Serge the sleeve seam allowances separately. Sew the sleeve seam from the top up to the mark for slit, press the seam apart. Sew sleeves into armholes, serge and press.
10. Sew a gathering stitch along the lower edge of sleeve and gather fullness. Fold the cuff piece in half

lengthwise with the right side facing inward and sew side edges. Start and stop stitching exactly at the marked line of the cuff seam. Turn the piece right side out, press. Sew outer side of cuff to sleeve, fold the seam allowance of the inner cuff inward and stitch in the seam attaching the outer cuff. Topstitch around the cuff, 0.5 cm from the edge.

11. Serge the seam allowance along the hem press onto wrong side and topstitch.

12. Work buttonholes on the right front piece and cuffs. Sew buttons onto the left front piece and cuffs.

TECHNICAL DRAWING:

