

Sewing Pattern — Jacket 5915

Recommended fabric: natural/mixed suiting fabric.

You will also need: fusible interfacing, 3 buttons.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: on hem of the garment 3 cm, all other seams 1 cm.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Center front – cut 2
2. Side front – cut 2
3. Center back – cut 2
4. Side back – cut 2
5. Front band – cut 2
6. Back neckline facing – cut 1
7. Belt – cut 1
8. Facing of front armhole – cut 2
9. Facing of back armhole – cut 2

Fusible interfacing:

1. Buttonstand/collar – cut 2
2. Back neckline facing – cut 1
3. Facing of front armhole– cut 2
4. Facing of back armhole– cut 2

INSTRUCTIONS:

1. Apply fusible interfacing to front band, back neckline facing, facings of back and front armhole.
2. Sew side fronts to center fronts; sew side backs to center backs. Serge seams and press toward center.
3. Sew center back seam. Serge seam and press toward left.
4. Sew side and shoulder edges. Serge seams and press toward back.
5. Sew front band to front. Press seams apart.
6. Sew the collar center back edge together. Serge seam and press toward left. Sew collar section of front band into the neckline of back, trim corners, clip into curves and press seams apart. Sew shoulder seams of back neckline facing and front band. Clip into curves and press seams apart. Serge outer edges of front band and back neck facing.
7. Place buttonstand/collar on front, right sides together, and sew buttonstand/collar of the garment. Understitch buttonstand seam allowance onto buttonstand. Stitch at 0.2 cm off the seam. Turn front stands onto right side, straighten seams. Tack seam allowances of facing and of back at 0.1 cm off the collar connecting seam. Tack the facing to shoulder and center seam by hand.
8. Serge and press the seam allowance onto hem of the garment. Sew lower corner of buttonstand and topstitch seam allowance onto garment.
9. Sew shoulder and side edges of the armhole facings. Press seams apart. Serge outer seam allowances. Place facing, right sides together, and sew to armhole. Trim, a clip into curves. Press seam toward facing and understitch. Turn to inside and tack the facing to shoulder and side seam by hand.
10. Make buttonholes on right front, sew buttons on left front.
11. Fold the belt in half lengthwise, right sides together, and sew on long and one short sides. Turn belt onto right side. Turn under open end of belt along seam allowance and slipstitch closed. Tack belt to left side seam.

TECHNICAL DRAWING: