

Sewing Pattern — Dress 4266

Recommendations on fabric: chiffon

You will also need: blind zipper, lining.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: hem of the dress – 2.0 cm, lower edges of flounces – 0 cm, lower edge of sleeve – 0 cm, all other seams – 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Side front part – 2 details
4. Central front part - 1 detail
5. Yoke – 1 detail
6. Sleeve - 2 details
7. Flounce_1 – 1 detail
8. Flounce_2 – 1 detail
9. Flounce_3 – 1 detail
10. Flounce_4 – 1 detail
11. Flounce_5 – 1 detail

Lining:

1. Central back part - 2 details
2. Side back part - 2 details
3. Side front part – 2 details
4. Central front part - 1 detail (connect central front part and yoke)

INSTRUCTIONS:

1. Sew princess seams on back part, press seam allowances to center seam and serge. Sew center seam of back part. Serge and press the seam.
2. Sew princess edges of front part, press seam allowances to center seam and serge.
3. Serge lower edges of flounces with thin rolled seam, slightly stretching the edge.
4. Press upper edges of flounces 1, 2 and 3 at 1 cm onto wrong side. Topstitch flounce-1 onto front part according to marking line. Put the seam along pressed edge at 1 mm off the fold. Then topstitch flounces 2 and 3 the same way. Put flounce-4 onto front part and fix along edges of the armhole, shoulder and neckline. Put flounce-5 onto front part on top of the flounce-4 and fix along edges of the armhole, shoulder and neckline.
5. Cut a bias tape, fold it in half lengthwise and shape a rose.
6. Stitch yoke to front part, inserting the rose into the seam. Serge and press the seam downwards.
7. Serge separately left side edge. Sew left side edge, leaving a section for zipper unsewn. Press apart the seam. Sew zipper in.
8. Sew right side and shoulder edges, press seam onto back part and serge.
9. Serge lower edge of sleeve with thin rolled seam, slightly stretching the edge. Sew the sleeve into the armhole. Press and serge seam allowances.
10. Sew lining the same way as main fabric details. Overstitch the neckline. Slash seam allowances, turn details out and press. Overstitch armhole in two steps: first armhole of front part, then armhole of back part. Fasten lining to zipper tape. Turn hem of lining twice at 1 cm and topstitch.
11. Overstitch hem of the garment with baby seam. To do that press seam allowance onto wrong side at 2 cm, stitch at 0.1-0.2 cm off the fold. Cut seam allowance off close to the stitch. Turn inside seam allowance once again and put the stitch on top of previous one. Press the seam.

TECHNICAL DRAWING:

