

Sewing Pattern — Dress 5893

Recommendations on fabric: fabric suitable for dress / silk

You will also need: fusible interfacing; invisible zipper; decorative closure

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance : all seams -1 cm, on hem of the garment – 1.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Back skirt - cut 2
2. Front skirt – cut 1
3. Upper front - cut 1
4. Shoulder strap – cut 4
5. Front neck trim/ facing – cut 2
6. Front trim/facing – cut 4
7. Back skirt trim/ facing – cut 4
8. Front skirt trim/facing – cut 2

Interfacing:

1. Shoulder strap – cut 2
2. Front neckline trim – cut 1
3. Back trim – cut 2
4. Front trim – cut 2
5. Front skirt trim– cut 1

INSTRUCTIONS:

1. Apply interfacing to listed pieces.
2. Serge edges of armholes of upper front, press seam onto wrong side, topstitch. Make a gathering stitch on top and lower edges of front and gather fullness.
3. For back closure: cut a square - 5x5 cm for straps from main fabric. Fold in half lengthwise, wrong sides together and press. Unfold, press side edges toward center and fold in half. Sew at 0.1 cm off the edge, cut into two pieces. Set straps into decorative closure (swimsuit fastener, etc).
4. Sew together interfaced pieces of front neckline trim, shoulder straps and front trim. Sew upper front to front neckline trim. Sew lower edge of upper front to front trim from edge up to marker. Press seam allowances onto trim.
5. Sew together facing pieces of front neckline facing, shoulder straps and front facing. Pin onto interfaced pieces and sew the front neckline, outer edge of shoulder straps and lower edge of front facing, inserting straps with closure. Clip into curves, turn right side out, press. Turn raw edges of the facing and shoulder straps under, match, and topstitch at 0.1 cm from the edge.
6. Sew side seams of the skirt, serge and press toward back.
7. Sew side seams of interfaced back trim and of outer front skirt trim. Make a gathering stitch on top edges of back and front skirt and gather fullness. Sew to interfaced back trim and to front skirt trim. Press the seam upwards.
8. Serge center edges of back skirt separately. Sew from zipper mark downwards, press seam allowances apart. Sew in zipper.
9. Sew back facing to front skirt facing, pin onto trim and sew on top edge, right sides together, inserting upper part of front between them. Turn facing to wrong side, press. Press inside raw edges of facing and topstitch into connecting seam of outer trim.
10. Serge lower edge of garment, press to wrong side, and topstitch.

TECHNICAL DRAWING:

