

Sewing Pattern — Dress 5891

Recommendations on fabric: light-weight denim or jeans fabric.

You will also need: companion fabric for facings and pockets, 3 buttons, invisible zipper.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: hem - 5 cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Front – cut 1
3. Yoke – cut 1
4. Placket (front Loop) – cut 1
5. Short strap – cut 2
5. Long strap – cut 2
6. Pocket bag – cut 2

Companion fabric:

1. Yoke – cut 1
2. Placket (front loop) – cut 1
3. Short strap – cut 2
4. Long strap – cut 2
5. Pocket bag – cut 2

INSTRUCTIONS:

1. Pin placket and straps with companion fabric, right sides together, Sew long sides and one short side. Turn placket and straps out and press. Sew a double topstitch at 0.1 and 0.7 cm along the edge. Make buttonholes on placket (front loop) and on long strap.
2. Pin yokes right sides together and sew armhole and upper edge, inserting short strap between yokes at marks for placement. Clip into curves, turn yoke out and press. Sew double stitch along top edge and armhole. Now work the yoke as one-layer detail.
3. Make a gathering stitch at 0.5 cm off the edge along the lower edge of the yoke. Gather between notches. Sew together yoke and front part. Trim seam, serge and press toward yoke.
4. Sew darts on back and press toward center. Sew back center seam. Serge and press toward left.
5. Cut bias tape of companion fabric of 9 cm wide to work top edge of back. The length of the bias tape is equal to top edge of back + 4 cm. Fold bias tape in half lengthwise wrong sides together and press. Sew the bias tape to top edge of back from the right side, inserting long strap into the seam. Fold bias tape to wrong side, trim seam allowances and press.
6. Stitch pocket bags to back / front, matching notches. To front -sew pocket bag of companion fabric, to back – of main fabric.
7. Serge hem separately on back and on front. Fold turnup seam allowance to right side of the front and back and sew side edges. Trim corners.
8. Right side seam: Sew back and front right sides together, inserting front into top between back and facing. Sew down to the mark, stitching together pocket bags at the same time. Trim the seam near top edge of pocket bag. Press section from top edge up to top edge of pocket bag to back and serge. Press apart section from top edge of pocket bag down to the slit opening and serge.
9. Left side seam: Serge separately left side edge on back and on front. Sew seam together from zipper mark, around pocket bags and down to slit opening. Press opening for zipper. Sew in zipper. Tack ends of back neckline facing to zipper tape.
10. On both pockets, sew pocket opening from lower edge of pocket bag up to the notch. Press pocket bags onto front part and topstitch according to markers.
11. Turn hem of front and back out, straighten corners and topstitch with double stitch. Double topstitch back neckline facing. Press.
12. Sew the placket (front loop) from the wrong side into yoke and front connecting seam. Adjust the length of the placket beforehand while trying on. Sew buttons on short strap and on front for front loop.

TECHNICAL DRAWING:

