

Sewing Pattern — Dress 5883

Recommendations on fabric: natural/mixed lightweight suiting fabric

You will also need: invisible zipper, lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Central back - 2 details
2. Side back - 2 details
3. Side front - 2 details
4. Central front - 1 detail

Lining:

1. Central back - 2 details
2. Side back - 2 details
3. Side front - 2 details
4. Central front— 1 detail

INSTRUCTIONS:

1. Serge center edge of back. Sew in zipper from top edge to notch. Turn back lower part of zipper and sew center edge of back from notch down. Press seam allowances apart.
2. Sew darts on front, starting the stitch exactly near center seam line, press seam allowances upwards. Sew center edge of front, press seam onto left side and serge.
3. Sew central and side fronts, press seam allowances toward center and serge.

4. Sew side and shoulder edges, press seam allowances of side edges toward back and serge, press apart seam allowances of shoulder edges.
5. Sew details of lining the same way as main fabric. Place lining and main fabric right sides together and neckline overstretch edge and armhole edges. Press seam allowances, clip on curves. Turn dress out, serge, press. Turn seam allowances of back center edge (lining) and tack to zipper tape. Turn lower edge of lining twice to wrong side and topstitch.
6. Press hem of the garment onto wrong side, turn inside at 1 cm and topstitch.

TECHNICAL DRAWING:

