

Sewing Pattern — Blouse 5874

Recommendations on fabric: natural or mixed blouse fabric (silk, viscose)

You will also need: invisible zipper, elastic thread

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: on hem of the garment – 1.5 cm, all other seams – 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back - cut 2
2. Front - cut 2
3. Sleeve – cut 4 (2 are for lining- cut of main fabric)
4. Collar – cut 1
5. Flounce – cut 2

INSTRUCTIONS:

1. Pin flounce (without cutting) right sides together, and sew along outer edge. Seam width is 0.7 cm. Cut flounce along marked line, trim seam allowances. Sew section from inner corner of the flounce



up to marker, slash seam allowance near marker, turn flounce out and press. Make a gathering stitch on right side along inner edge and gather lightly.

2. Sew darts on front. Press waist darts towards center and bust darts downward.
3. Sew darts on back. Press darts toward center. Sew center back seam. Serge and press seam toward left.
4. Sew flounce to center edge of right front: match notches on flounce to notches on center front. At 1.5 cm from lower edge of front, match lower corner of the flounce to this point. Adjust gathers and sew. Sew left and right fronts together, serge and press seam toward left.
5. Sew shoulders and right side seam, serge and press seam toward back. Serge left side edges separately. Sew left side seam from underarm to zipper notch. Press seam apart including opening for zipper. Sew in zipper.
6. Press collar in half lengthwise, then open, fold into ring, right sides together, and sew. Serge and press seam. Turn collar out and press. Sew outer collar into the neckline, turn inner side seam allowance under, and topstitch into collar connecting seam. Turn collar round with flounce-coquille and stitch corner of the flounce with wrong side into collar connecting seam.
7. Sew sleeve seam, serge and press. Insert lining of sleeve into the sleeve, right sides together, and sew along the lower edge. Press seam towards lining. Sew along lining connecting seam between markers with elastic thread, placing elastic on wrong side. Turn right side out, match upper edges and baste. Then sew the sleeve as one-layer detail. Make a gathering stitch between notches and gather fullness along sleeve cap. Sew sleeve into armhole, matching notches and adjusting gathers. Press seam towards back and front.
8. Serge lower edge of garment, press onto wrong side, and topstitch.

TECHNICAL DRAWING:

