

## Sewing Pattern — Roll-Neck with Decorative Sleeves 5866

Recommendations on fabric: middle/high stretchable jersey (natural or mixed).

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for the garment and sleeve hems, 0.7 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Front part – 1 piece
2. Back part – 1 piece
3. Back sleeve part – 2 pieces
3. Front sleeve part – 2 pieces
4. Inner collar part – 1 piece
5. Outer collar part – 1 piece

**ATTENTION!** Before starting work, sew the collar into a ring and check that you can put your hand through it.

**OUR ADVICE:** stitch jersey details with special elastic/zig-zag stitches or using a 3- or 4- thread overlock.

### **INSTRUCTIONS:**

1. Stitch shoulder and side front and back edges. Serge seam allowances and press them to the back.
2. Sew the inner collar into a ring. Sew the outer collar into a ring, make pleats. Put the inner and outer collar parts together wrong side out and stitch around the upper edge, turn out to the right side, press. Stitch in the collar into the neckline edge.
3. Make pleats on the sleeve parts (the inner pleat edge looks up). Stitch the upper and lower sleeve edges. Serge and press seam allowances.
4. Stitch sleeves into arm-holes. Making sure the notches coincide. Serge and press seam allowances.
5. Serge the garment and sleeve hems. Fold them to the wrong side, press and topstitch.

**TECHNICAL DRAWING:**

