

Sewing Pattern —Blouse 5864

Recommendations on fabric: natural or mixed knit fabric of high or medium stretchiness

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem and hem of sleeve - 1.5 cm, outer edge of flounces - 0 cm, other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 1 detail
2. Back part – 1 detail
3. Left sleeve – 1 detail
4. Front part of right sleeve – 1 detail
5. Back part of right sleeve – 1 detail
6. Flounce 1 – 1 detail
7. Flounce 2 – 1 detail
8. Flounce 3 – 1 detail
9. Collar – 1 detail

ATTENTION! Before sewing please check your head gets through stitched into ring collar.

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnout is stitched with twin needles to save stretchiness.

INSTRUCTIONS:

1. Stitch front and back parts of right sleeve to front part and back part armhole. Serge and press the seam.
2. Sew left shoulder edge of back and front parts. Serge and press the seam towards back part.
3. Fold collar in half lengthwise, wrong sides together. Stitch collar to neckline, leveling notches. Side edge of collar is near right shoulder seam. Serge and press collar connecting seam.
4. Fold flounces so that narrow one is from above, middle one is under it, then comes the widest one. Level edges and stitch loosely along inner edge. Gather ruffles (the length of gathering is mentioned on front part pattern). Outer edge of the flounce stays unsewn.
5. Fold front part and back part right sides together and level edges of collar, right shoulder edge and edge of sleeve. Insert the flounce between back and front halves, leaving 1.5 cm to lower edge of sleeve, near the collar bypass the flounce at 2 cm above collar. Narrow flounce is directed to front part, wide flounce — to back part. Sew edge of collar, shoulder edge and edge of sleeve. Turn bypassed part of the flounce onto wrong side and fasten by hand, closing collar connecting seam.
6. Sew side seams of back part and of front part, stitching right sleeve seam at the same time. Serge seams and press towards back part.
7. Sew left sleeve seam. Serge and press the seam.
8. Sew left sleeve into armhole, aligning notches. Serge and press the seam.
9. Serge hem of garment and lower edge of sleeve. Turn onto wrong side, press and topstitch. Start and finish the stitch on right sleeve near the flounce.

TECHNICAL DRAWING:

