

## Sewing Pattern — Tunic 5852

Recommendations on fabric: silk fabric suitable for dresses.

You will also need: bias tape, 2 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem - 3 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back part – 2 details
2. Front part – 1 folded detail
3. Placket – 1 detail
4. Placket\_1 – 2 details
5. Yoke – 1 detail

### **INSTRUCTIONS:**

1. Fold the placket in half lengthwise wrong sides together and press. Fold details of placket\_1 right sides together and overstitch lower shaped edge. Turn placket\_1 out and press.
2. Sew darts on front part. Press darts upwards. Make a counter pleat on front part. Press the pleat and fasten on top edge of front part and according to markers at waist level.
3. Stitch plackets to front part. Sew yoke to front part. Press the seam upwards and serge.
4. Sew shoulder seams. Press seams towards back part and serge.
5. Cut bias tape of 4 cm wide to work the armhole and neckline. Fold bias tape in half lengthwise wrong sides together and press. Fold the bias tape with the edge of the armhole from the right side and overstitch, fold the bias tape to wrong side and topstitch along the fold onto main detail. Press the seam. In the same way overstitch the neckline.

6. Overstitch pencil buttonhole. Stitch buttonhole to center edge of right back part. Serge central edges of back part. Sew center seam of back part from hem up to the notch and press apart. Fasten seam allowance of center edge to the neckline with 2-3 tacks.
7. Sew side seams. Serge seams and press towards back part. Fasten seam allowance of side seam to armhole with 2-3 tacks.
8. Press hem of the garment at 3 cm, then turn seam allowance again at 1 cm and topstitch.
9. Sew buttons on back part and on the yoke.

**TECHNICAL DRAWING:**

