

Sewing Pattern — Dress 5850

Recommendations on fabric: natural or mixed fabrics suitable for dresses

You will also need: blind zipper, piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along the edge of the dress – 3 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Central front part – 1 detail
4. Side front part – 2 details
5. Upper front part – 2 details
6. Lining of front part – 1 detail
7. Neckline facing– 2 details
8. Facing of the front part armhole– 2 details
9. Facing of the back part armhole – 2 details

INSTRUCTIONS:

1. Serge lower edge of front part lining.
2. Stitch loosely along lower edge of upper front part and gather ruffles. Stitch piping to top edge of front part, slashing it in corners. Fold front part and front part lining right sides together, insert upper front part between them. Sew. Turn onto right side and press.
3. Sew princess edges of front part, press seam allowances towards center and serge.
4. Sew darts on back part. Press depths towards center. Sew princess seams on back part, press seam allowances towards center and serge.
5. Serge central edges of back part. Sew center edge of back part up to zipper notch. Sew in zipper. Press seam allowances apart, pressing closure at the same time.

6. Sew shoulder and side edges. Serge seams and press towards back part.
7. Fold dress and the neckline facing right sides together and overstretch neckline edge, slash seam allowances on rounded parts. Direct seam allowance onto the facing and put the stitch along facing at 0.1 cm off the seam.
8. Sew side and shoulder edges of the armhole facing. Serge along outer edge. Fold dress and the facing right sided together and overstretch armhole, slash seam allowances on rounded parts. Direct seam allowance onto the facing and put the stitch along facing at 0.1 cm off the seam. Fix on shoulder and side seams.
9. Serge hem of the dress. Turn seam allowance a inside and undersew with invisible stitches by hand.

TECHNICAL DRAWING:

