

Sewing Pattern — Dress 5849

Recommendations on fabric: natural or mixed fabric suitable for dresses

You will also need: invisible zipper, lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm; on hem of the dress – 3.0 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Upper back - 2 details
2. Central lower back - 2 details
3. Side lower back - 2 details
4. Back inset – 1 detail
5. Upper front 1 detail
6. Central lower front - 1 detail
7. Side lower front - 2 details
8. Sleeve - 2 details

Lining:

1. Upper back part - 2 details
2. Upper front part – 1 detail

INSTRUCTIONS:

1. Sew waist darts on upper and lower backs. Press darts toward center of detail.
2. Stitch central lower back to upper back, press seam allowances upwards and serge.
3. Serge middle edge of back. Sew in zipper from top edge down to notch. Turn lower part of zipper and sew middle edge of back from notch downwards. Press seam allowances apart.
4. Put gathering stitch on top edge of back inset and gather ruffles. Stitch inset to back, press seam allowances upwards and serge. Connect side back, press seam allowances toward center and serge.
5. Stitch side front to lower front, press seam allowances toward center and serge.
6. Make pleats on upper front and stitch to lower part. Press the seam upwards and serge.
7. Fold sleeve in half lengthwise right sides together and stitch on long side, turn right side out and press. Put gathering stitch on unsewn edges and gather ruffles.
8. Sew details from lining the same way as main fabric details, serge lower edges and middle edge of back. Put lining on main garment right sides together, insert sleeves between them, and overstretch neckline and armhole edges, press seam allowances, clip into curves. Turn details right side out. Tack center seam allowance (on back lining) to zipper tape. Topstitch lower edges into main details connecting seam.
9. Sew side seams, press seam onto back and serge.
10. Turn seam allowance of the dress hem to wrong side at 1 cm and topstitch.

TECHNICAL DRAWING:

