

Sewing Pattern — Blouse 4259

Recommendations on fabric: natural or mixed knit fabric of medium stretchiness

You will also need: decorative cord, 4 caps for the cord, elastic of 2 cm wide

If the pattern has double contour the seam allowances are included.
Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams – 0.7 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 1 folded detail
2. Back part — 1 folded detail
3. Lower part — 1 folded detail
4. Cuff — 2 details

Advice:

Knitted fabric details are sewn together with special elastic or narrow zig-zag stitch. When serging cut seam allowances to 0.6 – 0.8 cm. Seam allowance on turnup is stitched with twin needles to save stretchiness. Details also can be sewn together via 3 or 4 – threaded serger.

INSTRUCTIONS:

1. Sew shoulder seams and top edges of sleeves. Serge seam allowances and press them towards back part. Sew side seams and lower edges of sleeves. Serge allowances and press them towards back part.
2. Cut the neckline facing of 6 cm wide, length is shown on front part pattern. Sew the facing into ring. Turn the facing out, fold in half right side out and press. Sew the elastic into ring. Insert the elastic into the facing and fix with temporary stitch along lower edge of the elastic, leaving seam allowances. Stitch the facing to the neckline, slightly stretching the facing. Seam is at left shoulder seam level. Remove temporary stitch.

3. Sew cuff into ring. Stitch loosely along lower edge of sleeve and gather ruffles. Fold cuff in half lengthwise and stitch to the sleeve. Serge seam allowance.
4. Sew lower part into ring. Fold lower part in half lengthwise and stitch to lower edge of the blouse, slightly stretching lower edge. Seam is at the left side seam level. Serge seam allowance.
5. Make a bow from decorative cord and sew by hand to the neckline at shoulder seams level. Put caps onto cords.

TECHNICAL DRAWING:

