

## Sewing Pattern — Blouse 5837

Attention: Collar is not adjacent to the neck. It is provided by the model.

Recommendations on fabric: natural or mixed blouse fabric (silk, viscose, mixed fabrics).

You will also need: interfacing, 5 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: on hem of the garment – 1.5 cm, all other seams – 1cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Central back - 2 details
2. Side back - 2 details
3. Central front - 2 details
4. Side front - 2 details
5. Sleeve – 2 details
6. Collar – 2 details
7. Stand part of collar – 2 details
8. Cuff – 2 details
9. Placket – 2 details

#### Interfacing:

1. Collar – 1 detail
2. Stand part of collar – 2 details
3. Placket – 2 details

## **INSTRUCTIONS:**

1. Apply interfacing to plackets, top collar and both stand parts of collar.
2. Fold top collar with lower right sides together. Overstitch ends and outer edge of collar. Trim seams. Turn collar out, straighten and press. Fold stand part details right sides together, set ready collar between them, level notches and sew, overstitching ends of stand part at the same time. Start and end stitch exactly near marked line of stand part connection seam. Turn ready collar out and press.
3. Sew darts on side front. Press darts to side seam and stitch up. Sew princess edges on front. Press seams to central part and serge.
4. Fold placket in half lengthwise right side out and press. Unfold the placket, put together with front right sides touching and stitch outer side of placket to front. Press seam towards placket. Turn inner side of placket inside and topstitch into connecting seam.
5. Sew darts on back. Press darts to center seam. Sew princess edges on back. Press seams to center seam and serge. Sew center edge of back. Press seam onto left side and serge.
6. Sew shoulder and side seams. Press seams to back and serge.
7. Sew top stand part of collar with collar into the neckline, turn inside open edge of lower stand part and topstitch into top stand part connecting seam.
8. Sew, press and serge edges of sleeves. Fold cuffs in half lengthwise right side out and press. Unfold cuffs and sew them into ring right sides together. Press and serge seam. Fold cuffs on fold line and stitch to hem of sleeve. Serge seam and press it upwards. Make and fasten pleats on sleeve according to marks. Inner depths of pleats are directed towards center of sleeve. Sew sleeves in. Press seam towards armhole and serge.
9. Serge hem of the garment, press onto wrong side and topstitch.
10. Serge buttonholes on right front, sew buttons on left front.

## **TECHNICAL DRAWING:**

