

Sewing Pattern — Short coat 5835

Recommendations on fabric: fabric suitable for coats

You will also need: fusible interfacing, 13 buttons (not less than 2 cm in diameter), lining, shoulder pads, sleeve heads

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams; 3 cm for the garment hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center upper back – cut 2
2. Side upper back – cut 2
3. Lower back – cut 1
4. Side upper front – cut 2
5. Side lower front – cut 2
6. Center front – cut 2
7. Upper sleeve – cut 2
8. Lower sleeve – cut 2
9. Stand-up collar – cut 2
10. Front band facing – cut 2
11. Flap – cut 4
12. Cuff – cut 2
13. Strap – cut 2
14. Back neck facing – cut 1
15. Shoulder strap – cut 2
16. Loop – cut 1
17. Decorative button loop – cut 3

Lining:

1. Upper back – cut 2
2. Lower back – cut 1
3. Front – cut 1
4. Upper sleeve – cut 2
5. Lower sleeve – cut 2
6. Pocket bag – cut 4

Fusible interfacing:

1. Center front– cut 2
2. Stand-up collar – cut 1
3. Front band facing – cut 2
4. Flap – cut 2
5. Cuff – cut 2
6. Strap – cut 2
7. Back neck facing – cut 1
8. Shoulder strap – cut 2

INSTRUCTIONS:

1. Apply the interfacing to wrong side of listed pieces.
2. Pin the flap, right sides together, and sew the outer edge. Trim the corners, turn right side out, and press. Make a decorative stitch 0.7 cm from the edge. Sew pocket bags to the flap.
3. Sew the side upper front and lower front right sides together, press seam apart and topstitch at 0.7 cm from the seam.
4. Pin the pocket bag on the right side of the side front, pin the flap with the attached pocket bag to the center front matching the notches right side down. Sew the pocket bag to the pocket entrance seam allowance. Turn up the side front seam and topstitch it onto the pocket bag.
5. Sew the side front and the pocket bag to center front. Slash the seam allowance at the pocket entrance ends, press the curved seam allowances toward the center pressing the pocket at the same time. Make decorative stitch at 0.7 cm along the curved seam up to the waist.
6. Sew the back center seam, press seam allowance to the left and topstitch at 0.7 cm from the seam. Sew the side backs to center back, press seam allowances towards the center and topstitch at 0.7 cm from the seam. Sew lower back to the upper back, press seam allowances apart and topstitch at 0.7 cm from the seam.
7. Sew the shoulder and side seams, press seam allowances apart.
8. Sew the back neck facing to the front band facings, press seam allowances apart.
9. Sew the outer collar to the garment neckline, sew the inner collar to the facing, clip into curves and press seams apart. Pin facing to garment, right sides together and sew along center front edges and the stand-up collar with one seam. Trim corners, turn and press.
10. Fold strap in half lengthwise, right sides together, and sew around the long and curved edges. Trim corners, turn the strap right side out, and press. Make decorative stitch at 0.7 cm along the edge, whipstitch the buttonhole.
11. Sew the front sleeve seam, press seam apart.
12. Press the cuff in half lengthwise, right side out. Unfold cuff and sew outer edge to lower edge of sleeve, press the seam toward the cuff and topstitch at 0.7 cm from the seam. Sew sleeve elbow seam, simultaneously sewing the cuff and inserting the strap.
13. Make a gathering stitch along sleeve cap for ease. Sew the sleeve into the armhole matching notches and adjusting ease.
14. Pin shoulder straps right sides together and sew around the long and curved edges. Trim corners, turn right side out, and press. Make decorative stitch at 0.7 cm along the edge, whipstitch the buttonhole. Serge the open edge.

15. Fold the button loop three times lengthwise and sew with flatlock stitch. Cut it in two and serge the edges. ADVICE: If it is not possible to make flatlock stitch, coat fabric loop can be faced with lining. Ready loop width is 1 cm.
16. Sew the loop and the shoulder strap to the shoulder as indicated in technical drawing.
17. Sew in shoulder pads and sleeve pads.
18. Sew lining same as main fabric, leaving an opening in the right sleeve seam for turning. Pin the lining and the garment right sides together, and sew to the inner edges of facing. Press stand-up collar seam apart. Stitch in seam allowances and pin them close to the seams. Sew horizontally across the lower front band facing, trim corners. Mark and press garment hem. Sew lining to hem. Sew sleeve lining to the inner cuff. Turn the garment right side out through the opening in the right sleeve seam and sew the opening closed.
19. Fold decorative button loop three times lengthwise and stitch with flatlock stitch. Try the button loop on the garment; cut extra fabric and serge the edges. ADVICE: If it is not possible to make flatlock stitch, coat fabric button loop can be lined. Ready button loop width is 1 cm.
20. Whipstitch the buttonhole and sew button on collar. Sew buttons in accordance with button loops.

TECHNICAL DRAWING:

